



## Alternate Catalog No. DP30C2P-1 Catalog No. 1SBX103200R1200

Description: DP CONTR,30A,2P,120/60

UPC No 662019749464

 $\label{loss:eq:home} \mbox{Home} > \mbox{Contactors} \ \& \ \mbox{Starters} > \mbox{Definite Purpose Contactor}$ 

DP30C2P-1 DP contactor provide outstanding performance in various HVAC, Food service equipment, refrigeration and welding applications and meet all relevant standards, including UL, CSA and IEC. Industry standard mounting plate provides easily accessible mounting holes.

Descriptors	
Category	Definite Purpose Contactor
	·
Specifications	
Product Type	DP Contactor
Amps Frame	30 A
Poles	2P
Coil Voltage	120 V
Bulk Pack	Single
Special Termination	Standard
Order Multiple	1
Termination	#10-32 combo screw with Quad quick connector
UL / cUL Certification  Dimensions	UL / cUL _ E224401
Length	2.07 in.
Width	3.26 in.
Height	2.36 in.
Weight	0.6 lb.
Operating Performance	
Operating temperature	-40+65 oC
Insulation Class	130 oC Class B
Ordering	
Customs Tariff Number	85365080

electrification.us.abb.com Created on: 09/30/2024

electrification.us.abb.com Created on: 09/30/2024