

Alternate Catalog No. PSR9-600-11
Catalog No. 1SFA896105R1100

Description: PSR SSTR,600V/24V AC/DC,9A

UPC No 7320500477168

Home > Soft Starters > Softstarter - Open (PSR)

PSR softstarter - The compact rangeThe PSR softstarter range is a simple yet reliable starting solution that utilizes only the most basic of soft starting features: soft start and stop. It performs well in applications requiring many starts per hour and is perfect for installations where you need to save space.**Main benefits*** Small and compact starting solution* Can perform many starts per hour* Reduce energy loss at full speed with built-in bypass.**Main features*** Rated operational current: 3 to 105 A* Operational voltage: 208-600 V AC* Control supply voltage: 24 V AC/DC or 100-240 V AC.



Descriptors

| | |
|----------|--------------------------|
| Category | Softstarter - Open (PSR) |
|----------|--------------------------|

Specifications

| | |
|---------------------------------------|---------------|
| Product Type | Soft Starters |
| Input Voltage | 208-600 V |
| Control Voltage | 24Vac/dc |
| Normal Duty: Output Current (A) | 9 |
| Normal Duty: Motor Power (HP) at 460V | 5 |
| Power Dissipation In Watts | 6.5 |
| Height (Inches) | 5.5 |
| Width (Inches) | 1.8 |
| Depth (Inches) | 4.5 |

Classifications

| | |
|----------------|-----|
| RoHS Indicator | Yes |
| UL/CUL Listing | Yes |

Dimensions

| | |
|-------------|-------|
| Weight (lb) | 0.99 |
| Height (mm) | 140 |
| Width (mm) | 45 |
| Depth (mm) | 113.5 |
| Weight (kg) | 0.45 |