

GC15A, Mechanical Grounding Connector, Cable to Water Pipe, #14-1/0 AWG, 1/2"-1" Pipe, AI/Cu Rated

By Burndy Catalog # GC15A

Mechanical Grounding Connector, Cable to Water Pipe, 14 AWG - 1/0 AWG, 1/2" - 1" Pipe, Al/Cu Rated.



Features

- Dual-rated for both copper and aluminum conductors providing maximum flexibility
- Tin-plated to provide contact resistance and prevent galvanic corrosion
- Clamps are range taking, only 3 catalog numbers cover the complete range of applications from 1/2 to 4 inches
- UL467 Listed

Application

For Use With Either Copper Or Aluminum Conductors To Copper Water Pipe, Galvanized Pipe Or Steel Conduit

General

GC15A Catalog Number **EU RoHS Indicator** Yes Installation Torque 180 LBS/in

Recommended in-lb

Material Aluminum Steel Material Type - Screw Physical Attribute - Screw Slot

Type

Plated Plating Type Tin

Sub Brand MECHANICAL CONNECTOR

-0.4 Temperature Rating

Type GC-A, Dual Rated UPC 781810240007 UPC 12 Digit 7818102400077

Dimensions

Dimension - Hole Size inch 0.40 in Dimension - Hole Size mm 10 mm Dimension - L Length Overall 57 mm mm 2.25 in Dimension - Length Overall

Dimension - Pad Width inch 0.69 in Dimension - Width fraction 11/16 in Dimension - Width inch 0.69 in Dimension - Width mm 18 mm

Electrical Ratings

Voltage - Maximum 600 V

Conductor Related

Conductor - AL Str Size 8 AWG;6 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0

AWG;2/0 AWG;3/0 AWG;4/0 **AWG**

Conductor - AL Str Size 8 AWG-4/0 AWG

Range

Conductor - Copper Solid Size 14 AWG;13 AWG;12 AWG;11

AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG

Conductor - Copper Solid Size 14 AWG-1/0 AWG

Range

Conductor - Copper Str Size 14 AWG;12 AWG;10 AWG;9

> AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1

AWG;1/0

1/2;3/4;1

1/2 - 1

Conductor - Copper Str Size

Range

Conductor - Pipe or Round

Tube Run

Conductor - Pipe or Round

Tube Run Range

Conductor Type

· AL C Str-Size

14 AWG - 1/0 AWG

CU C Solid-Size

• CU C Str-Size

• Pipe or Tube Round-Run

Certifications And Compliance

Certification - FTI Certification - UL Listed Direct No Burial

Industry Standard(s) Standards - Industry

Standards Met

Standards - RoHS Compliance

Status **UL** Listed

Yes

UL467

UL467

Logistics

Carton Quantity 250 Minimum Pack Quantity

Product Assets

3D Models - GC15A MODEL-IGES 3D Models - GC15A MODEL-STEP

3D Models - GC15A MODEL-PDF

Catalogs - Full Line BURNDY Catalog Catalogs - Section E2 - Mechanical Grounding Customer Notices - Prop 65 Notice Product Cross Section Image(s) - BUR_GC22A_Lineart Sales Drawings - sc212057-01



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved. BRDY-GC15A-SPEC-EN | REV 6/2024