












Features:

- · Manufactured in type 304 stainless steel
- · Provides exceptional tensile strength and the highest levels of durability in harsh /corrosive environments
- · Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- · All connectors include an embedded Buna-A O-Ring
- · All connectors include a stainless steel Locknut
- · No package qty. required

Certifications and Compliances:

- · UL 514D Listed
- CSA Certified
- · Buy American Compliant
- · NEMA 4X Approved



Applications:

Stainless Cord Grips completely eliminate pull tension on terminals, control cable arc-of- bend, prevent cord pull-out, and provide a liquid-tight seal. All connectors can be ordered with or without wire mesh attachments and accommodate conduit sizes from 1/2" to 2".

Industries Commonly Served:

- Food & Beverage Production & Distribution
- · Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- · Petrochemical
- Pulp & Paper Mills
- Marine & Coastal Facilities

Trade Size	A (Body Bore)	В	C		D	L (Range)		F (Nut Dia.)
1/2"	0.610"	1.250"	0.540	" 1.	.270"	8-3/4" - 11-1/2"		1.520"
3/4"	0.810"	1.250"	0.560	" 0	.960"	8-3/4" - 11-1/2"		1.520"
1"	0.990"	1.750"	0.570	" 1.	.460"	13-1/4" - 14-1/2"		1.720"
1-1/2"	1.430"	2.250"	0.690	" 1.	.810"	13-1/4" - 14-1/2"		2.470"
2"	2.000"	2.830"	0.800	" 2	.320"	14-3/4" - 16-3/4"	· · · · · · · ·	2.970"

All dimensions are for informational purposes only *Tolerances +/- 5%