


Power lock industrial grade locking devices

Product description


3-pole, 4-wire grounding
30A, 480V/AC
Non-NEMA



20445N



20444N



20443N

Industrial grade plugs & connectors

Rating A	V/AC	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.	
30	480	Auto grip nylon	0.40-1.06" (10.2-27.0mm)	RD	□ 20445N	□ 20444N	•
		Armored	0.49-0.61" (12.3-15.5mm)	RD	□ 20445	□ 20444	•

Industrial grade receptacles

Rating A	V/AC	Description	Color	Single receptacle	
30	480	Industrial receptacles	BK	□ 20443N	•

Accessories for 50A locking devices & power lock devices in FS/FS boxes

Description	Color	Catalog no.	
Glass-filled nylon lift lid cover for 50A locking devices	Y	□ 7788CR	•
Glass-filled nylon lift lid cover for 4-wire 30A receptacles	GY	□ 20416N [†]	•

[†]Only UL Listed & CSA certified



7788CR



20416N

Dimensional information:
C-82, C-83

Plug & connector specification information:
Power lock: C-94

Receptacle specification information:
Power lock: C-95

Color information:

BK (Black), RD (Red), Y (Yellow)



Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32