





GE
Lighting

20853 - 300PAR56/NSP

GE PAR56 - Narrow Spot



CAUTIONS & WARNINGS

Warning

- Risk of Fire
 - Keep combustible materials away from lamp.
- Risk of Electric Shock
 - Turn power off before inspection, installation or removal.
- Unexpected lamp rupture may cause injury, fire, or property damage
 - Use in enclosed fixture rated for this product.
 - Avoid direct water/liquid contact.

NOTES

- For use with heat-resistant connector supported by bulb rim or metal shell of base.
- Lamp is made of heat resistant glass (HRG).

GENERAL CHARACTERISTICS

| | |
|---------------------|---|
| Lamp Type | Sealed Beam - PAR |
| Bulb | PAR56 |
| Base | Extended Mogul End Prong (GX16d EXT) |
| Filament | CC-13 |
| Rated Life (NOM) | 2000.0 h |
| Primary Application | Narrow Spot |

PHOTOMETRIC CHARACTERISTICS

| | |
|--|---------|
| Initial Lumens (NOM) | 3450.0 |
| Center Beam Candlepower (CBCP) (NOM) | 40000.0 |
| Nominal Initial Lumens per Watt (NOM) | 11.5 |

ELECTRICAL CHARACTERISTICS

| | |
|---------------|-------|
| Wattage (NOM) | 300.0 |
| Voltage (NOM) | 230.0 |

DIMENSIONS

| | |
|---------------------------------------|--------------------|
| Maximum Overall Length (MOL) (NOM) | 5.000 in(127.0 mm) |
| Bulb Diameter (DIA) (NOM) | 7.000 in(177.8 mm) |

PRODUCT INFORMATION

| | |
|-------------------------------------|----------------|
| Product Code | 20853 |
| Description | 300PAR56/NSP |
| Standard Package | Case |
| Standard Package GTIN | 10043168208533 |
| Standard Package Quantity | 12 |
| Sales Unit | Unit |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard Package | 12 |
| UPC | 043168208536 |