



BURNDY Catalog Number	K2A40U
UPC Number	781810600252
Description	TWO:300-800 DUAL RATED
Status	Active

Web Use
BURNDY Product Line

Dimensional	
Width (in)	3.19
Length (in)	3.38
Bolt Hole Size (in)	0.63
Thickness	0.5
D - in	1.66
Pad Width (in)	3.2
N (in)	0.88
General	
Number of Conductors	2
Number of Holes	1
Product Description	Aluminum Universal Terminal, 2 Conductor, 1 Hole, 300-800 kcmil, 5/8" Stud, 2 Screws, Al/Cu Rated, Tin Plated
Conductor(s)	
Aluminum Size (Range)	300 kcmil-800 kcmil
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	300 kcmil-800 kcmil
Physical	
Installation Torque	500
Type of Plating	Unplated
Connector Type	Terminal
Bolt Hole Size	5/8
Plated (Yes or No)	N
Product Material	Aluminum
Approvals / Certifications	
Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Exempt
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA
47, industrial Park Drive
Manchester NH03109

BURNDY Technical Servcies
47, industrial Park Drive
Manchester NH03109

Hours: 8.00 AM - 5.00 PM
Monday - Friday
Phone: 000-346-4175

