


Complex environment locking devices

Product description


4-pole, 4-wire non-grounding
30A, 3ØY 120/208V/AC
Non-NEMA



Receptacle Plug



L1830PW



L1830RW

3ØY plugs & connectors

Rating A	V/AC	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.	
30	120/208	3ØY watertight	0.43-1.15" (10.9-29.2mm)	Y	□ 3431PW	□ 3433CW	
		3ØY watertight	0.43-1.15" (10.9-29.2mm)	BK	□ 3431PWBK	□ 3433CWBK	
		3ØY severe duty	0.63-1.16" (15.9-29.4mm)	Y & BK	□ 3431PY	□ 3433CY	


3ØY receptacles

Rating A	V/AC	Description	Color	Single receptacle catalog no.	
30	120/208	3ØY watertight	Y	□ 3433RW	
		3ØY watertight	BK	□ 3433RWBK	

Complex environment locking devices

Product description

4-pole, 4-wire non-grounding
30A, 3ØY 120/208V/AC
NEMA L18-30



L18-30R L18-30P

3ØY plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
30	120/ 208	L18-30	3ØY watertight	0.43-1.15" (10.9-29.2mm)	Y	□ L1830PW	□ L1830CW		
			3ØY watertight	0.43-1.15" (10.9-29.2mm)	BK	□ L1830PWBK	□ L1830CWBK		
			3ØY severe duty	0.63-1.16" (15.9-29.4mm)	Y & BK	□ L1830PY	□ L1830CY		

3ØY receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.		
30	120/ 208	L18-30	3ØY watertight	Y	□ L1830RW		
			3ØY watertight	BK	□ L1830RWBK		

Dimensional information:
D-34-35

Specification information:
Watertight industrial plugs & connectors: D-38
Watertight industrial receptacles: D-39
Severe duty industrial plugs & connectors: D-40

Color information:

BK (Black), Y (Yellow)



Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32