

Rittal – The System.

Faster – better – everywhere.

► Wall-mounted cooling units TopTherm "Blue e" Total cooling output 0.50 – 0.75 kW – SK 3361.540

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-mounted cooling units TopTherm "Blue e" Total cooling output 0.50 – 0.75 kW – SK 3361.540

created: 24.05.2018 build on www.rittal.com/us-en



Product description	
Material:	Carbon steel
Color:	RAL 7035
Protection category IP to IEC 60 529:	External circuit, IP 34 Internal circuit, IP 54
Supply includes:	Nano-coated condenser Wired ready for connection (plug-in terminal strip) Drilling template Fasteners External toroidal core transformer
Note:	The technical specifications for the wall-mounted cooling unit 3361.540 are valid with an external transformer connected.
Product features	
Total cooling output to DIN EN 14511:	L 35 L 35 at 50 Hz: 0.85 kW (2900 BTU) L 35 L 35 at 60 Hz: 0.89 kW (3036 BTU) L 35 L 50 at 50 Hz: 0.67 kW (2286 BTU) L 35 L 50 at 60 Hz: 0.67 kW (2286 BTU)
Air throughput (unimpeded air flow):	External circuit: 550 m³/h (323.7 cfm) Internal circuit: 230 m³/h (135.4 cfm)
Rated operating voltage:	400 V, 2~, 50 Hz/60 Hz Note: External toroidal core transformer Ø 126 x 65 mm deep for mounting in the enclosure.

Dimensions:	Height: 550 mm (22 ") Width: 280 mm (11 ") Depth: 280 mm (11 ")
Temperature control:	e-Comfort Controller (factory setting +35°C)
Temperature range:	Operation (environment): +10°C...+55°C Operating temperature (max.) 60 Hz: +53°C Setting range: +20°C...+55°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 280 g (9.9 oz) Global Warming Potential (GWP): 1430 CO ₂ equivalent (CO ₂ e): 0.4 t
Rated power Pel:	L 35 L 35 at 50 Hz: 0.4 kW L 35 L 35 at 60 Hz: 0.43 kW L 35 L 50 at 50 Hz: 0.47 kW L 35 L 50 at 60 Hz: 0.5 kW
Rated current (max.):	At 50 Hz: 1.2 A At 60 Hz: 1.4 A
Start-up current (max.):	At 50 Hz: 3.1 A At 60 Hz: 3.3 A
Pre-fuse:	Transformer circuit-breaker: 6,3 A...10 A
Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:	2.08
Packaging unit:	1 pc(s).
Weight/packaging unit:	22 kg (48.5 lb.)
EAN:	4028177433755
Customs tariff number:	84158200
ETIM 6.0:	EC000855
ETIM 5.0:	EC000855
eCl@ss 8.0/8.1:	27180704
eCl@ss 7.0/7.1:	27180704
eCl@ss 6.0/6.1:	27180704
eCl@ss 5.1/5.1.4:	27180704

Product description (long):	SK cooling unit Blue e, wall-mounted, 0.85 kW, 400 V, 2~, 50/60 Hz, Sheet steel, WHD: 280 x 550 x 280 mm
Approvals	
Approvals:	CSA TÜV-Geprüfte Leistung TÜV-Geprüfte Sicherheit UL + C-UL - FTTA UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity Declaration of conformity - F-gas regulation