

Product Number:	49171
Order Abbreviation:	QTP1X28T5UNVPSNNL
General Description:	1-lamp Universal Voltage electronic ballast for 28W T5 lamp, packaged 20 pieces per case, without leads



Product Information

Abbrev. With Packaging Info.	QTP1X28T5UNVPSNNL 20/CS 1/SKU
Ballast Factor	1.00
Ballast Height H (in)	0.8660
Ballast Length L (in)	14.1340
Ballast Width W (in)	1.1810
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.30
Nominal Voltage (V)	120-277V
Number of Lamps	1
Open Circuit Voltage (V)	<600
Power Factor	>0.98
Primary Lamp Type	FP28T5
Sound Rating	A
Starting Method	PROSTART
Starting Temperature - Fahrenheit	0
Starting Temperature - Celsius	-18
Total Harmonic Distortion (THD)	<10%
Wiring Method	WIRETRAP CONNECTORS



Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 18 feet
- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Ground ballast case
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Minimum Starting Temperature: 0F/-18C.
- Input Frequency: 50/60Hz.
- Complies with UL935 requirements for "Type CC" rating

