

EDSR-23

Brand Features

PowerSwitch SDS devices meet NEC Article 430 for separate disconnect in-sight of motor loads and OSHA Title 29 CFR 1910 and 1926 for lockout, tag out protection. The complete PowerSwitch SDS package is non-metallic, watertight and is engineered to enhance safety and performance for critical power control installations.

Item Description

30 Amp Non-Fused PowerSwitch Safety Disconnect Switch with Locking Receptacle Bracket, Rated IP54 & IP66.

Technical Information

Product Features

IP Rating: IP 54 Splashproof

Type: Non-Fused

Amperage: 30 A

Voltage: 600 VAC

HP Rating: Receptacle Dependant

Pole: 2, 3, or 4

t_{sa}_auxiliary_contact: Factory Installed; N.O. 10A; Early Break-Late Make

Fuse Type: NA

Body Material: Valox 357

Handle Material: Valox 357

t_{sa}_external_hardware: Stainless Steel

Color: Gray

Standards and Certifications: UL/CSA

Warranty: 2 Year Limited

Flammability: Rated V-0 per UL 94

Features and Benefits


- Accepts 20A or 30A, up to 600V, V-0 Max Locking Receptacles (sold separately)
- 4 Mounting feet included (5 position settings)
- Space provided for bottom or top conduit entry
- Captive Stainless Steel screws won't fall out when cover is open
- Bottom hinge mechanism pivots 180 degrees for easy access during installation and maintenance
- Rated to IP54, Type 3R standards when cover is closed
- Rated to IP66, Type 4X standards when used with Wetguard seal package and Plugs
- EDSR-23 supplied with: a) Ground Bracket and Green Wire b) 5 pieces of wire accommodating all receptacle - switch connections (1-white, 1-green, 3-black) c) Receptacle Voltage Labels: After receptacle installation, select the matching amperage/voltage combination label and affix to enclosure label. d) Wetguard seal package for use with corrosion resistant receptacles and Wetguard Plugs



Color:  Gray

UPC Code: 07847724204

Country Of Origin: Mexico



SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
<input type="text"/>	<input type="text"/>	<input type="text"/>
JOB NUMBER:	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

