

BALDOR® • RELIANCE

Product Information Packet

CDP3330

.5HP,1750RPM,DC,56C,3336P,TENV,F1

Part Detail							
Revision:	V	Status:	PRD/A	Change #:		Proprietary:	No
Type:	DC	Prod. Type:	3336P	Elec. Spec:	33WGZ122	CD Diagram:	CD0194
Enclosure:	TENV	Mfg Plant:		Mech. Spec:	33-2024	Layout:	33LY2024
Frame:	56	Mounting:	F1	Poles:	00	Created Date:	
Base:	RG	Rotation:	R	Insulation:	F	Eff. Date:	05-27-2011
Field Type:		Literature:		Elec. Diagram:		Replaced By:	

Specs			
Enclosure:	TENV		
Frame:	56C		
Frame Material:	Steel		
Agency Approvals:	CE		
	CSA		
	UR		
Base Indicator:	Rigid		
Bearing Grease Type:	Polyrex EM (-20F +300F)		
Drip Cover:	No Drip Cover		
Duty Rating:	CONT		
Feedback Device:	NO FEEDBACK		
Heater Indicator:	No Heater		
Insulation Class:	F		
Lifting Lugs:	No Lifting Lugs		
Motor Lead Quantity/Wire Size:	2 @ 18 AWG, A		
Motor Lead Exit:	Ko Box		

Motor Lead Termination:	Flying Leads		
Mounting Arrangement:	F1		
Product Family:	General Purpose		
Pulley End Bearing Type:	Sealed Bearing		
Shaft Extension Location:	Pulley End		
Shaft Ground Indicator:	No Shaft Grounding		
Shaft Rotation:	Reversible		
Shaft Slinger Indicator:	No Slinger		
Motor Standards:	NEMA		

Nameplate NP0891L											
CAT.NO.		CDP3330									
SPEC.		33-2024Z122									
HP		.5				ENCL		TENV			
RPM		1750									
FRAME		56C				TYPE		3336P			
ARM V		90				ARM A		4.8			
FLD V						FLD A					
INSUL		F				AMB.		40			
DUTY		CONT				SUPPLY		1.3			
BRG/DE		6203				BRG/ODE		6203			
BRUSHES		2/BP5011T01									
						BLANK					
SER.											
BLANK											
APRV-CE		Y		APRV-CSA		Y		APRV-UL		Y	

DC Motor Performance Data

Record # 2408 - Typical performance - not guaranteed values

Winding: 33WGZ122-R001	Type: 3336P	Enclosure: TENV
-------------------------------	--------------------	------------------------

Nameplate Data		General Characteristics	
Rated Output (HP)	0.5	Armature Resistance @ 25°C	1.163 Ω
R.P.M.	1750		
Armature Volts	90	Voltage Constant	47.81 v/krpm
Armature Amps	4.8		
Field Volts		Armature Inductance	14.506 mH
Field Amps		Armature Inertia	14.05 LI ²
Rating - Duty	40C AMB-CONT		
Form Factor	1.3		

Load Characteristics at 90 Armature Volts

Load Point	1	2	3	4	5	6	7
Armature Amps	0.26	1.45	2.56	3.62	4.65	5.79	7
R.P.M.	1853	1777	1721	1658	1629	1579	1519
Torque (LB-FT)	0	0.38	0.76	1.14	1.5	1.9	2.28

Performance Graph at 90.0 Arm V, 0.5HP Typical performance - Not guaranteed values





