

Technical data sheet · LÜTZE ELECTRONIC PLTC PVC with UL/CE/PTLC Approvals



Flexible electronic cable · Unshielded

Identification	Type	LiYY PLTC PVC 4×AWG22
	Part-No.	A3032204

Use/Application/Characteristics

Application	• Industrial grade PLTC electronic cable for machine tools, process instrumentation and controls, computer peripherals, HVAC technology, assembly and production lines, low voltage interconnect and other industrial applications including installation in cable trays
Characteristics	• Flexible for easy installation • Easy strip design • Color coded conductors • Specially formulated jacket for oil resistance • Premium durability • Extended temperature range • UL listed and NFPA 79 compliant

Construction

Description	ELECTRONIC PLTC PVC
Number of conductors/cross-section	4×AWG22
Jacket material	PVC
Jacket color	grey RAL 7001
Outer Ø	4.9 mm
Outer Ø	0.193 inches
Weight	26 Lbs/Mft

14.08.2018 – Subject to technical modification

Part-No. A3032204

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk

Technical data sheet · LÜTZE ELECTRONIC PLTC PVC with UL/CE/PTLC Approvals

Cu-Index 9 Lbs/Mft

Element 1

Element construction	AWG22/4C
Conductor construction	AWG 22 (19/34)
Conductor	AWG conductor CU-wire tin-plated
Conductor category	fine wire
Conductor marking	black brown red orange
Conductor insulation	SR-PVC

overall construction

Jacket characteristics	Flame-retardant Oil resistant Silicone-free
------------------------	---

Technical data

Rated voltage UL	300 V
Temperature range fixed	-25 °C ... +105 °C
Minimum bending radius fixed	4×D

Element 1

Element construction	AWG22/4C
----------------------	----------

Approvals/Standards

Approvals	cULus PLTC UL Type CM cURus AWM II A/B NEC 725, 760, 800 Class 1 Div. 2 (PLTC use only)
UL style	AWM 2464
Conformity	CE REACH RoHS
Burning behavior according to	UL VW-1 UL FT4
Oil resistant according to	Oil Res II

14.08.2018 – Subject to technical modification

Part-No. A3032204

USA: LÜTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY


Technical data sheet · LÜTZE ELECTRONIC PLTC PVC with UL/CE/PTLC Approvals

General

Note

CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

Symbols



14.08.2018 – Subject to technical modification

Part-No. A3032204

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY