



MORRIS CAT#: 23294-23299

24-14 AWG Push-In Lever Type Wire Connectors



Features:

- Easy Push-In Wire Connectors are simple to install - instead of Twisting or Taping, simply Push Wires Into Contact Port to save you time and money
- Accepts Either Stranded or Solid Wire
- Low Wire Insertion Force allows fast, easy connections
- No-Twist Connection reduces repetitive motion fatigue
- See-thru for visual connection inspection
- Test Port for Continuity Testing
- Electrolytic Tin-Plated Internal Copper Bus for high conductivity
- Housing Material: Polycarbonate, UL 94V-2 flame retardant
- Current: 24A or 32A
- Voltage: 600V
- Working Temperature: 221°F (105°C)
- UL Listed for Copper Conductors only

24-12 AWG Push-In Lever Type Wire Connectors



DIMENSIONS = INCHES

CAT. NO.	PORTS	VOLTS	AMPS	WIRE RANGE SOL/STR	L	W	H	BOX/PAIL QTY	CASE QTY
INNER BOX									
23294	2	24-12	32	24-12	.81	.51	.42	100	6,000
23295	3	24-12	32	24-12	.81	.73	.42	50	3,000
23296	5	24-12	32	24-12	.81	1.17	.42	25	1,500
BULK PAIL									
23297	2	24-12	32	24-12	.81	.51	.42	6,000	6,000
23298	3	24-12	32	24-12	.81	.78	.42	4,000	4,000
23299	5	24-12	32	24-12	.81	1.17	.42	2,300	2,300