


Designer Bullet Flood 120-277 Volt




BULLET FLOODS




- Lumileds LUXEON 3030 2D
- CRI: 84+
- 114 Lumens/Watt
- Power Factor: .97+
- 1/2" NPT Knuckle Mount
- Isolated Driver Compartment for Optimal Thermal Management
- Corrosion Resistant Die Cast Aluminum Housing
- Superior Architectural Powder Coat Finish
- Fluted Reflector & Polycarbonate Lens
- Photocontrol (not included) can be Installed Remotely
- Input Voltage: 120-277VAC
- 35° Beam Angle available in 15W & 28W
- 65° Beam Angle available in 15W, 28W, & 42W
- Operation Temperature: -40°F to 131°F
- 50,000+ Hour LED Life Expectancy
- IP65 (Nema 4) Watertight
- cULus Listed
- DLC Listed
- 5 Year Warranty



15 Watt



28 Watt



42 Watt

Cat. No.	Watts	Color Temperature	Color	Delivered Lumens	Beam Angle	CRI	Replaces Halogen	Weight (Lbs)	Case Qty
----------	-------	-------------------	-------	------------------	------------	-----	------------------	--------------	----------

Spot Floods - 35° Beam Angle

71660	15	5000K Cool White	Bronze	1620	35	83	100W	1.5	12
71663	28	5000K Cool White	Bronze	3022	35	83	2 X 100W	2.5	8

Floods 65° Beam Angle 15 Watt

71675	15	3000K Warm White	Bronze	1536	65	84	100W	1.5	12
71676	15	3000K Warm White	Green	1536	65	84	100W	1.5	12
71677	15	3000K Warm White	Black	1536	65	84	100W	1.5	12
71678	15	3000K Warm White	White	1536	65	84	100W	1.5	12
71679	15	5000K Cool White	Bronze	1620	65	83	100W	1.5	12
71680	15	5000K Cool White	Green	1620	65	83	100W	1.5	12
71681	15	5000K Cool White	Black	1620	65	83	100W	1.5	12
71682	15	5000K Cool White	White	1620	65	83	100W	1.5	12

Floods 65° Beam Angle 28 Watt

71683	28	3000K Warm White	Bronze	2724	65	84	2 X 100W	2.5	8
71684	28	3000K Warm White	Green	2724	65	84	2 X 100W	2.5	8
71685	28	3000K Warm White	Black	2724	65	84	2 X 100W	2.5	8
71686	28	3000K Warm White	White	2724	65	84	2 X 100W	2.5	8
71687	28	5000K Cool White	Bronze	3022	65	83	2 X 100W	2.5	8
71688	28	5000K Cool White	Green	3022	65	83	2 X 100W	2.5	8
71689	28	5000K Cool White	Black	3022	65	83	2 X 100W	2.5	8
71690	28	5000K Cool White	White	3022	65	83	2 X 100W	2.5	8

Floods 65° Beam Angle 42 Watt

71691	42	3000K Warm White	Bronze	4204	65	83	3 X 100W	4	6
71692	42	3000K Warm White	Green	4204	65	83	3 X 100W	4	6
71693	42	3000K Warm White	Black	4204	65	83	3 X 100W	4	6
71694	42	3000K Warm White	White	4204	65	83	3 X 100W	4	6
71695	42	5000K Cool White	Bronze	4488	65	83	3 X 100W	4	6
71696	42	5000K Cool White	Green	4488	65	83	3 X 100W	4	6
71697	42	5000K Cool White	Black	4488	65	83	3 X 100W	4	6
71698	42	5000K Cool White	White	4488	65	83	3 X 100W	4	6