


## 10" 30W COMMERCIAL DOWNLIGHT










Part#	Housing Color	Wattage	Lumens	сст	Voltage	Input Current @ 120V	Lumens/ Watt	Energy Star
72667	White	30W	2900	5000K	120-277	.2454A	96	Yes

## **PHOTOMETRY**



www.morrisproducts.com



## 10" 30W **COMMERCIAL DOWNLIGHT**

Mounting: Ceiling Mount

## **Technical Specifications:**

Frequency: 60Hz

CCT: 5000k (Cool White)

Chromaticity (x,y): x=.4638; y=.4123

30 Watts

CRI: ≥ 82.2

LED: SSC3030

**Operating Temperature: Electrical:** 

Minimum Starting -31° - 122° F Input Voltage: 120 thru 277

Current: .2454A @ 120V **Construction:** 

Power Factor: ≥.9 Housing: Aluminum Housing

White Trim

**Product Parameters:** IP Rating: IP43 Wet Indoor Location Rated

Efficacy: 96 lumens per watt Lens Material: Frosted Polycarbonate Lens

50,000+ LED Life Span

(Drywall / Sheetrock)

**Chromacity Measurements:** 

Beam Angle: 35° Listings: UL, Energy Star BUG Rating: N/A

R9: 8 Carton Qty: 1

DUV: 0.00034 Weight: 7 lb

Chromaticity (u,v): u=.2642; v= .3524 Warranty:

Morris Products carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal

and proper usage).

**Component Specifications:** 

Driver: 120-277V 50-60HZ **Driver Output Volts:** 

**Driver Output Amps:** Surge Protection: 2500V

Dimming: 0-10 Dimming