

Wall Mount Occupancy/Vacancy Sensor - Double Pole - PIR



- ▶ The Passive Infrared (PIR) sensor detects motion by sensing the difference between body heat and ambient room temperature
- ▶ Wall switch works best in offices, conference rooms and commonly used areas
- ▶ Vacancy Setting allows for Manual ON/Auto OFF Function
- ▶ LED indicator for visibility in darkened rooms
- ▶ 30Ft Range When Mounted 4Ft Height
- ▶ Adjustable Light Level Sensitivity Settings
- ▶ Time delay Off setting is adjustable from 5 Seconds to 30 minutes
- ▶ Removable Cover with mode settings and dip switch adjustments
- ▶ Decorator Wall Plate Included
- ▶ Compatible with Incandescent, Electronic Ballast Fluorescent, Compact Fluorescent, Magnetic Low Voltage, Electronic Low Voltage, LED lighting
- ▶ Button 1: Manual On/Auto Off Button 2: Standby & OCC/VAC Selectable
- ▶ Conforms to California Title 24 Energy Code
- ▶ **Neutral Required**

Cat. No.	Color	Switch Type	Switch Configuration	Incandescent/Fluorescent Rating	Coverage	Voltage	Case Qty
80544	White	On/Off Auto Manual On/Auto Off	Double Pole	800W@ 120V	180°	120	50
80548	White	On/Off Auto Manual On/Auto Off	Double Pole 3 Way	800W @ 120V 1200W @ 277V	180°	120-277	50

Ceiling Sensor Switch - PIR



- ▶ The Passive Infrared (PIR) sensor detects motion by sensing the difference between body heat and ambient room temperature
- ▶ Adjustable Light Level Sensitivity Settings
- ▶ Auto ON/OFF
- ▶ Time delay Off setting is adjustable from 15 seconds to 30 minutes
- ▶ No ground required
- ▶ Compatible with Incandescent, Electronic Ballast Fluorescent, Compact Fluorescent, Magnetic Low Voltage, Electronic Low Voltage, LED lighting
- ▶ Polycarbonate
- ▶ Conforms to California Title 24 Energy Code
- ▶ No Separate Power Pack Required

Cat. No.	Color	Incandescent/Fluorescent Rating	Coverage	Voltage	Case Qty
80552	White	800W@ 120V 1200W@ 277V	360° 20 Ft Diameter @ 15 Ft Height 15 Ft Diameter @ 10 Ft Height	120-277	50

High/Low Bay Occupancy Sensor - PIR



- ▶ The Passive Infrared (PIR) sensor detects motion by sensing the difference between body heat and ambient room temperature
- ▶ Adjustable Light Level Sensitivity Settings
- ▶ Time delay Off setting is adjustable from 15 seconds to 30 minutes
- ▶ No ground required
- ▶ Compatible with Incandescent, Electronic Ballast Fluorescent, Compact Fluorescent, Magnetic Low Voltage, Electronic Low Voltage, LED lighting
- ▶ Polycarbonate
- ▶ Conforms to California Title 24 Energy Code
- ▶ No Separate Power Pack required

Cat. No.	Color	Incandescent/Fluorescent Rating	Coverage	Voltage	Case Qty
80556	Light Gray	800W@ 120V 1200W@ 277V	360° - 30Ft Height & 40Ft Diameter	120-277	50