

DATA -VOICE CABLE**Cat5e -Enhanced Category 5 UTP****Plenum/CMP/MPP****CONSTRUCTION**

Conductor	- Solid annealed Bare copper
Insulation	- Plenum: FEP (Fluorinated Ethylene Propylene)
Jacket	- Plenum: low smoke PVC (Polyvinyl Chloride)

Applications:

- 4 Mbps Token Ring (IEEE 802.5)
- 10 Mbps 10 BASE-T ETHERNET (IEEE 802.3)
- 16 Mbps Token Ring (IEEE 802.5)
- 100 Mbps (ANSI X3T9.5 TPDDI)
- 100 VG ANYLAN (IEEE 802.12)
- 100Mbps 100 BASE-T Fast ETHERNET (IEEE 802.3)
- 155 Mbps ATM
- 622 Mbps ATM
- 1000 Mbps 1000 BASE-T Gigabit ETHERNET (IEEE 802.3)

Standards:

- ETL/UL Available
- ANSI/ICEA S-90-661-1997
- ANSI/TIA/EIA 568-A
- FCC PART 68

Part #	AWG	Pairs	Nom. O.D.	Lbs./M'
J452404	24	4	.197"	21

* Available Jacket Colors -Black, Green, Blue, Yellow, Gray, and White.

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.