



# ALR 37/56 mm

GBE 20W 12V 18DEG 50PK

Delivers high lumen output and excellent color rendering for precise accent and display lighting. Philips Halogen Aluminum Reflector Lamps provide continuous color and high luminous intensity for precise accent and display lighting. These lamps offer a rated average life ranging from 2000 hours and feature excellent beam qualities for accent or ambient lighting.

## Product data


General Information	
Cap-Base	BA15D [ BA15d]
Philips Code	6434/FR
Operating Position	Universal [ Universal]
ANSI Code Halogen	GBE
Light Technical	
Beam Angle (Nom)	18 °
Luminous Intensity (Max)	1000 cd
Correlated Color Temperature (Nom)	3000 K
Color Rendering Index (Nom)	100
Operating and Electrical	
Power (Rated) (Nom)	20.0 W
Lamp Current (Nom)	1.67 A
Starting Time (Nom)	0.0 s
Voltage (Nom)	12 V
Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Finish	Frosted (FR)
Cap-Base Information	na [ -]
Luminaire Design Requirements	
Bulb Temperature (Max)	250 °C
Cap-Base Temperature (Max)	350 °C
Product Data	
Order product name	GBE 20W DC Bay 12V 18D FR 1CT
EAN/UPC - Product	046677340025
Order code	340026
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	924007717119
Net Weight (Piece)	17.900 g
ILCOS Code	HMGII/F-20-12-B15d-37/18



ALR 37/56 mm


Dimensional drawing



Alu 37mm 6434/FR 20W BA15d 12V 18D FR

Product	D (max)	C (max)
GBE 20W DC Bay 12V 18D FR 1CT	38 mm	41 mm

Photometric data



Aluline 37/56 20W 18D

