

# Power supply unit - UNO-PS/1AC/24DC/ 30W - 2902991

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Primary-switched UNO POWER power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/30 W

## Product Description

UNO POWER power supplies with basic functionality

Thanks to their high power density, compact UNO POWER power supplies are the ideal solution for loads up to 240 W, particularly in compact control boxes. The power supply units are available in various performance classes and overall widths. Their high degree of efficiency and low idling losses ensure a high level of energy efficiency.

## Your advantages

- Flexible mounting by simply snapping onto the DIN rail
- More space in the control cabinet with up to 20 % higher power density
- Maximum energy efficiency, thanks to over 90 % efficiency and extremely low idling losses under 0.3 W
- Outdoor installation, thanks to the wide temperature range from -25°C to +70°C



## Key Commercial Data

|              |               |
|--------------|---------------|
| Packing unit | 1 pc          |
| GTIN         |               |
| GTIN         | 4046356729192 |

## Technical data

### Dimensions

|        |         |
|--------|---------|
| Width  | 22.5 mm |
| Height | 90 mm   |
| Depth  | 84 mm   |

### Ambient conditions

|  |  |
|--|--|
| Degree of protection                       | IP20   |
| Ambient temperature (operation)            | -25 °C ... 70 °C (> 55 °C Derating: 2.5 %/K) |
| Ambient temperature (start-up type tested) | -40 °C                                       |
| Ambient temperature (storage/transport)    | -40 °C ... 85 °C                             |

# Power supply unit - UNO-PS/1AC/24DC/ 30W - 2902991

## Technical data

### Ambient conditions

|  |                                   |
|--|-----------------------------------|
| Max. permissible relative humidity (operation) | ≤ 95 % (at 25 °C, non-condensing) |
| Climatic class                                 | 3K3 (in acc. with EN 60721)       |
| Degree of pollution                            | 2                                 |

### Input data

|                                     |   |
|-------------------------------------|---|
| Nominal input voltage range         | 100 V AC ... 240 V AC                     |
| Input voltage range                 | 85 V AC ... 264 V AC                      |
| Current consumption                 | 0.8 A (100 V AC)                          |
|                                     | 0.4 A (240 V AC)                          |
| Nominal power consumption           | 72.1 VA                                   |
| Inrush surge current                | < 20 A (typical)                          |
| Mains buffering                     | typ. 25 ms (120 V AC)                     |
|                                     | typ. 115 ms (230 V AC)                    |
| Input fuse                          | 2 A (slow-blow, internal)                 |
| Choice of suitable circuit breakers | 6 A ... 16 A (Characteristics B, C, D, K) |
| Power factor (cos phi)              | 0.47                                      |
| Type of protection                  | Transient surge protection                |
| Protective circuit/component        | Varistor                                  |

### Output data

|  |  |
|--|--|
| Nominal output voltage                         | 24 V DC ±1 %                                     |
| Nominal output current (I <sub>N</sub> )       | 1.25 A (-25 °C ... 55 °C)                        |
| Derating                                       | 55 °C ... 70 °C (2.5%/K)                         |
| Connection in parallel                         | Yes, for redundancy and increased capacity       |
| Connection in series                           | yes  |
| Feedback resistance                            | < 35 V DC  |
| Protection against surge voltage on the output | ≤ 35 V DC  |
| Control deviation                              | < 1 % (change in load, static 10 % ... 90 %)     |
|  | < 2 % (Dynamic load change 10 % ... 90 %, 10 Hz) |
|  | < 0.1 % (change in input voltage ±10 %)          |
| Residual ripple                                | < 60 mV <sub>PP</sub> (with nominal values)      |
| Output power                                   | 30 W   |
| Typical response time                          | < 1 s  |
| Maximum power dissipation in no-load condition | < 0.3 W  |
| Power loss nominal load max.                   | < 5 W  |

### General

|                                 |                        |
|---------------------------------|------------------------|
| Net weight                      | 0.15 kg                |
| Efficiency                      | typ. 87 % (120 V AC)   |
|                                 | typ. 88 % (230 V AC)   |
| Insulation voltage input/output | 4 kV AC (type test)    |
|                                 | 3 kV AC (routine test) |

# Power supply unit - UNO-PS/1AC/24DC/ 30W - 2902991

## Technical data

### General

|                            |  |
|----------------------------|--|
| Protection class           | II (in closed control cabinet)                 |
| Degree of protection       | IP20   |
| MTBF (IEC 61709, SN 29500) | > 1158000 h (40 °C)                            |
| Mounting position          | horizontal DIN rail NS 35, EN 60715            |
| Assembly instructions      | alignable: 0 mm horizontally, 30 mm vertically |

### Connection data, input

|                                       |                     |
|---------------------------------------|---------------------|
| Connection method                     | Screw connection    |
| Conductor cross section solid min.    | 0.2 mm <sup>2</sup> |
| Conductor cross section solid max.    | 2.5 mm <sup>2</sup> |
| Conductor cross section flexible min. | 0.2 mm <sup>2</sup> |
| Conductor cross section flexible max. | 2.5 mm <sup>2</sup> |
| Conductor cross section AWG min.      | 24                  |
| Conductor cross section AWG max.      | 14                  |
| Stripping length                      | 8 mm                |
| Screw thread                          | M3                  |

### Connection data, output

|                                       |                     |
|---------------------------------------|---------------------|
| Connection method                     | Screw connection    |
| Conductor cross section solid min.    | 0.2 mm <sup>2</sup> |
| Conductor cross section solid max.    | 2.5 mm <sup>2</sup> |
| Conductor cross section flexible min. | 0.2 mm <sup>2</sup> |
| Conductor cross section flexible max. | 2.5 mm <sup>2</sup> |
| Conductor cross section AWG min.      | 24                  |
| Conductor cross section AWG max.      | 14                  |
| Stripping length                      | 8 mm                |
| Screw thread                          | M3                  |

### Standards and Regulations

|                                  |   |
|----------------------------------|---|
| Electromagnetic compatibility    | Conformance with EMC Directive 2014/30/EU |
| Noise immunity                   | EN 61000-6-2:2005                         |
| Connection in acc. with standard | CUL                                       |
| Standards/regulations            | EN 61000-4-2                              |
| Contact discharge                | 4 kV (Test Level 2)                       |
| Standards/regulations            | EN 61000-4-3                              |
| Frequency range                  | 80 MHz ... 1 GHz                          |
| Test field strength              | 10 V/m                                    |
| Frequency range                  | 1.4 GHz ... 2 GHz                         |
| Test field strength              | 3 V/m                                     |
| Standards/regulations            | EN 61000-4-4                              |
| Comments                         | Criterion B                               |
| Standards/regulations            | EN 61000-6-3                              |

# Power supply unit - UNO-PS/1AC/24DC/ 30W - 2902991

## Technical data

### Standards and Regulations


|  |   |
|--|---|
|  | EN 61000-4-6  |
| Frequency range  | 10 kHz ... 80 MHz   |
| Voltage  | 10 V (Test Level 3)   |
| Standards/regulations  | EN 61000-4-11   |
| Low Voltage Directive  | Conformance with LV directive 2006/95/EC  |
| Standard - Safety of transformers  | EN 61558-2-16   |
| Standard - Electrical safety   | IEC 60950-1/VDE 0805 (SELV)   |
| Standard – Electronic equipment for use in electrical power installations and their assembly into electrical power installations | EN 50178/VDE 0160 (PELV)  |
| Standard – Safety extra-low voltage  | IEC 60950-1 (SELV) and EN 60204-1 (PELV)  |
| Standard - Safe isolation  | DIN VDE 0100-410  |
| Standard – Limitation of mains harmonic currents   | EN 61000-3-2  |
| UL approvals   | UL/C-UL listed UL 508   |
|  | UL/C-UL Recognized UL 60950-1   |
|  | NEC Class 2 as per UL 1310  |
|  | UL/C-UL Listed ANSI/ISA-12.12.01 Class I, Division 2, Groups A, B, C, D T4 (Hazardous Location) |
| Shock  | 18 ms, 30g, in each space direction (according to IEC 60068-2-27)                               |
| Vibration (operation)  | < 15 Hz, amplitude ±2.5 mm (according to IEC 60068-2-6)   |
|  | 15 Hz ... 150 Hz, 2.3g, 90 min.   |
| Approval - requirement of the semiconductor industry with regard to mains voltage dips   | EN 61000-4-11   |
| Information technology equipment - safety (CB scheme)  | CB Scheme   |

### Environmental Product Compliance

|            |   |
|------------|---|
| REACH SVHC | Lead 7439-92-1  |
| China RoHS | Environmentally Friendly Use Period = 25;   |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Drawings

Block diagram



## Approvals

Approvals

# Power supply unit - UNO-PS/1AC/24DC/ 30W - 2902991

## Approvals

### Approvals

UL Recognized / IECEE CB Scheme / UL Listed / cUL Listed / cUL Recognized / EAC / EAC / UL Listed / UL Recognized / cUL Recognized / IECEE CB Scheme / cUL Listed / EAC / EAC

### Ex Approvals

UL Listed / cUL Listed / UL Listed / cUL Listed

### Approval details

|                 |  |   |                          |
|-----------------|--|---|--------------------------|
| UL Recognized   |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 214596            |
| IECEE CB Scheme |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a>   | DK-30305-A3-M1-UL        |
| UL Listed       |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 123528            |
| cUL Listed      |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 123528            |
| cUL Recognized  |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 214596            |
| EAC             |  |   | RU C-<br>DE.A*30.B.01082 |
| EAC             |  |   | RU C-<br>DE.A*30.B.01082 |
| UL Listed       |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 123528            |

# Power supply unit - UNO-PS/1AC/24DC/ 30W - 2902991

## Approvals

|               |  |   |               |
|---------------|--|---|---------------|
| UL Recognized |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 214596 |
|---------------|--|---|---------------|

|                |  |   |               |
|----------------|--|---|---------------|
| cUL Recognized |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 214596 |
|----------------|--|---|---------------|

|                 |  |   |                   |
|-----------------|--|---|-------------------|
| IECEE CB Scheme |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | DK-30305-A3-M1-UL |
|-----------------|--|---|-------------------|

|            |  |   |               |
|------------|--|---|---------------|
| cUL Listed |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 123528 |
|------------|--|---|---------------|

|     |  |  |               |
|-----|--|--|---------------|
| EAC |  |  | EAC-Zulassung |
|-----|--|--|---------------|

|     |  |  |               |
|-----|--|--|---------------|
| EAC |  |  | EAC-Zulassung |
|-----|--|--|---------------|

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>