

Flexible Conduits & Fittings T&B Catalog Number:

SVND-M638GT

UPC Number: 78620997360

Status: Active

Description:

PMAFIX straight grey connector with universal safety clip. Material - polyamide 6, thread type - metric, thread size -M63 x 1.5, conduit size NW - 48

- 48.	, tillodd oleo moo x mo, comdan oleo mm
Application	
	For cable protection systems in a wide range of applications
Characteristics	
	Vary high impact registeres
	Very high impact resistance Vibration proof connection to PMAFLEX conduits
	High conduit pull-out strength
	Very good chemical properties
	Free from halogens and cadmium
	Fits both conduit profiles - Fine (T) and coarse (G)
	Easy installation, simply push the conduit in
	Can be easily re-opened with a screwdriver
General	can ac cash, to spenda man a coloniame.
2 2 3 3 2 1 3 1	
Material	Polyamide 6
Color	Grey
Thread Type	Metric
Compatiable With	PMAFLEX, PMA Smart Line
Dimension Information	
Fits to Conduit Size (NW)	48
Fits to Conduit Size (metric)	50
Fits to Conduit Size (inches)	1 1/2
Thread Size (Metric)	M63 x 1.5
Technical Information	
Temperature Range-Continuous (Celsius) -40 degree C to +105 degree C
Temperature-Short-Term (Celsius)	+160 degree C
Technical Data Sheet	Available on Website
Chemical Resistance Chart	Available on Website
Specifications	
_	
3dmodel	Available on Website
IP Ratings	
IP Rating	IP66 stat. / IP54 dyn.
Packaging	
T&B Order Multiple	10
T&B Inner Pack	10
Package in Units	40
T&B Sold in UOM	Each
T&B Weight Per UOM	0.16 lbs. Each
Application Support	
PMA Reference Guide	Available on Website
Prouduct Overview-PMAFIX Connectors	
	Available on Website



PMAFIX Connectors-Safety and Sealing Systems

Certifications

RoHS Compliance

Yes

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com