



Bullhorn bracket safely supports HID floodlights. Great with Floodzilla, Mega flood and Flex flood models.

Color: Bronze

Weight: 34.9 lbs

Project:

Type:

Prepared By:

Date:

Technical Specifications

Construction

Finish:

Formulated for high durability and long-lasting color

Bullhorns:

3 tenons for slip fitters. Bullhorns fit 2 3/8" (6cm) O.D. tenons and accommodate 2 3/8" (6cm) slip fitters. Steel tubing.150" and.200" thick welded with (4) 3/8" bolts for securing to pole.

Slipfitters & Wall Brackets:

3/16" thick steel with 1/2" nuts and bolts

Bracket EPA:

2.0.

Weight:

25.6 lbs

Maximum Weight Capacity:

90 lbs per arm.

EPA Maximum Capacity:

4.0 per arm

Other

Patents:

The designs of fixtures are protected under U.S. and international intellectual property laws.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Technical drawing of a U-shaped metal part. The drawing shows a cross-section of the part with the following dimensions:

- Overall width: 30" (76.2cm)
- Radius of the U-shape: 18 1/4" (46.4cm)
- Thickness of the material: 2 3/8" (6cm)
- Height of the vertical stem: 2 3/8" (6cm)
- Overall height: 2 3/8" (6cm)
- Fit: 2 3/8" O.D. 6cm Tensol

Easy, secure floodlight mounting

Double Reinforced weld joints