

Technical data sheet · LÜTZE SUPERFLEX[®] TRONIC (C) PUR TP

Shielded electronic cable UL recognized, paired

For highest requirements



PUR electronic cables · C-track compatible ·
Shielded

Identification	Type	SU TR (C) PUR TP (10×2×0,25)
	Part-No.	117175

Use/Application/Properties

Application	• C-track as well as everywhere where signals are transmitted to continuously moving system or machine parts • Machine and device construction, transport and conveyor technology, heating, climate technology • In dry and damp rooms • As monitoring, measurement and control cable for continuous flexing applications • Especially for industrial environments with high EMI potential in machine, plant and device construction
-------------	--

17.04.2020 – Subject to technical modification

Part-No. 117175

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223

www.lutze.com · info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2

www.lutze.com · sales.gb@lutze.co.uk

Technical data sheet · LÜTZE SUPERFLEX[®] TRONIC (C) PUR TP

Shielded electronic cable UL recognized, paired

For highest requirements

Properties	• High active and passive interference resistance (EMC) • High crosstalk attenuation due to twisted pairs • Braided shield optimised for continuous flexing applications • Low capacitance, very good electrical properties • Flame-retardant, self-extinguishing • Halogen-free, no corrosive gases • Very good alternating bending strength • Low adhesion, abrasion-resistant, nick-resistant, tear resistant • Hydrolysis-resistant, microbe-resistant, and rot-resistant • Good ruggedness and salt water resistance • Excellent coolant and lubricant resistance • Resistant to most oils, greases, alcohol-free benzines and kerosene • Silicone free • RoHS-compliant
------------	--

Construction

Description	SUPERFLEX [®] TRONIC (C) PUR TP
Number of conductors/cross-section	(10×2×0.25)
Cross-section AWG	AWG 24
Cross-section, metric	0.25 mm ²
Jacket material	PUR
Jacket color	grey RAL 7001
Outer Ø	10.5 mm
Outer Ø	0.413 inch
Surface	adhesion-free matt
Weight	12.4 kg/100 m
Weight	121.9 Lbs/Mft
Cu-Index	7.9 kg/100 m
Cu-Index	53 Lbs/Mft

Element 1

Element construction	(10×2×0.25)
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 6 Superfinely stranded DIN VDE 0295 class 6
Conductor marking	Color coded
Conductor marking standard	DIN 47100
Conductor insulation	Special TPE

17.04.2020 – Subject to technical modification

Part-No. 117175

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SUPERFLEX[®] TRONIC (C) PUR TP

Shielded electronic cable UL recognized, paired

For highest requirements

overall construction

Overall stranding	stranded pairs layer pitch optimised conductors twisted without mechanical stress
Overall wrapping	Fleece taping
Overall shield	braid shield tinned copper wires optical cover approx. 85%
Jacket characteristics	Flame-retardant self-extinguishing Halogen free Oil resistant grease-resistant petrol-resistant (alcohol-free) kerosene-resistant Silicone-free

Technical data

Rated voltage	300 V V
Test voltage type	AC 1500 V
Temperature according to UL	80 °C
Temperature range moving	-25 °C ... +80 °C
Temperature range fixed	-40 °C ... +80 °C
Minimum bending radius moving	12×D
Minimum bending radius fixed	6×D

Element 1

Element construction	(10×2×0.25)
Insulation resistance at 20 °C	1000 MΩ×km

Certifications/Standards

Certifications	cURus
Conformity	CE RoHS
Burning behavior according to	IEC 60332-2-2 DIN EN 60332-2-2 UL 1581 UL Horizontal Flame Test UL FT2
Oil resistant according to	DIN EN 50363-10-2
Halogen free according to	IEC 60754-1 DIN EN 60754-1

17.04.2020 – Subject to technical modification

Part-No. 117175

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SUPERFLEX[®] TRONIC (C) PUR TP

Shielded electronic cable UL recognized, paired

For highest requirements

UV-resistant according to

UL 1581/2556-300h

General

Note

UL AWM Style 20233 or UL AWM Style 20549

Note

CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

Logo



17.04.2020 – Subject to technical modification

Part-No. 117175

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk