



Product Number: 49135

Order Abbreviation: QTP2X54T5/HO UNV PSN HT

General Description: 2-lamp Universal Voltage high ambient electronic ballast for 54W T5HO lamp with pre-inserted lead wires, packaged 10 pieces per case

Product Information

Abbrev. With Packaging Info.	QTP2X54T5HOUNVPSNHT 10/CS 1/SKU
Ballast Factor	1
Ballast Height H (in)	0.9450
Ballast Length L (in)	16.6930
Ballast Width W (in)	1.1570
Circuit Type	Series
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	1.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Power Factor	>0.98
Primary Lamp Type	FP54T5HO
Sound Rating	A
Starting Method	PROStart
Starting Temperature - Fahrenheit	-20
Starting Temperature - Celsius	-29
Total Harmonic Distortion (THD)	<10%
Wiring Method	Leads



QUICK60+SM
2121PM V.0.0.0.0.11

QUICKSENSESM
.. .. .

PROStartTM
PROGRAMMED START

Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 10 feet
- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Ground ballast case
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Input Frequency: 50/60Hz.
- Minimum Starting Temperature: 32F/0C.