



BL67 base module
1 × M23 Connector, 19-pin
BL67-B-1M23-19



Wiring Diagram



Functional principle

The pin resp. signal assignment results from the combination with an electronic module. You find the pin configuration and the wiring diagrams on the data sheet of the corresponding electronic module.

BL67 base modules are connected to the right of the gateway, using two screws for each module. A DIN rail is not required. This way, a compact and stable unit is built. The unit can now be mounted on a DIN rail or directly on the machine.

The field devices are connected to the base modules which are available with different connection technology (M8, M12, M23 and 7/8").

Note

Further technical data like temperature range are determined by the electronic modules and can be found on the data sheets.

Type designation	BL67-B-1M23-19
Ident-No.	6827216
Housing material	Polycarbonate, flame resistance (PC V0)
Housing color	Gray (RAL 7015)
Tightening torque fixing screw	0.9...1.2 Nm
DIN rail mounting	yes, Attention: Offset
Direct mounting	Two mounting holes, 6 mm Ø
Connector A	Female Receptacle, M23 × 1, Threaded
Housing material/finish	Brass, CuZn, Nickel-plated
Contact carriers	Plastic, PBT UL94-V0, White
Contacts	Metal, CuZn, Gold-plated
Panel seal	fluor caoutchouc, FPM
Insulation resistance	$\geq 10^{12} \Omega$
forward resistance	$\leq 3 \text{ m}\Omega$
Pollution degree	3/2
Number of contacts	19
Ampacity	10A contacts 6, 12, 19 and 4 A remaining contacts
Rated voltage	150 V
Protection class	When coupled - IP67, Only when screwed or plugged together