

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :					
Product line	: W22 Close Coupled Pump JP NEMA Premium Efficiency Three-Phase	Product code :	12598486		
		Catalog # :	00318ET3E182JP-W22		
Frame	: 182/4JP	Cooling method	: IC411 - TEFC		
Insulation class	: F	Mounting	: F-1		
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)		
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line		
Altitude	: 1000 m.a.s.l.	Approx. weight ²	: 91.5 lb		
Protection degree	: IP55	Moment of inertia (J)	: 0.3401 sq.ft.lb		
Design	: B				
Output [HP]	3	3	3	3	
Poles	4	4	4	4	
Frequency [Hz]	60	50	50	50	
Rated voltage [V]	208-230/460	380	400	415	
Rated current [A]	8.65-7.82/3.91	4.60	4.48	4.43	
L. R. Amperes [A]	70.1-63.3/31.7	29.0	31.4	33.2	
LRC [A]	8.1x(Code K)	6.3x(Code H)	7.0x(Code J)	7.5x(Code J)	
No load current [A]	3.45-4.00/2.00	2.00	2.15	2.25	
Rated speed [RPM]	1760	1445	1450	1455	
Slip [%]	2.22	3.67	3.33	3.00	
Rated torque [ft.lb]	8.83	10.8	10.7	10.7	
Locked rotor torque [%]	229	180	210	240	
Breakdown torque [%]	340	260	290	320	
Service factor	1.25	1.25	1.25	1.25	
Temperature rise	80 K	80 K	80 K	80 K	
Locked rotor time	41s (cold) 23s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	
Noise level ²	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	
Efficiency (%)	25%	86.4	87.2	87.3	87.3
	50%	87.5	87.5	87.5	87.5
	75%	88.5	87.5	87.5	87.5
	100%	89.5	87.5	87.5	87.5
Power Factor	25%	0.36	0.42	0.39	0.36
	50%	0.61	0.68	0.64	0.61
	75%	0.73	0.79	0.76	0.73
	100%	0.79	0.83	0.81	0.79
Bearing type	: <u>Drive end</u> 6307 ZZ <u>Non drive end</u> 6206 ZZ	Foundation loads			
Sealing	: V'Ring V'Ring	Max. traction	: 175 lb		
Lubrication interval	: - -	Max. compression	: 267 lb		
Lubricant amount	: - -				
Lubricant type	: Mobil Polyrex EM				
Notes					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	22/01/2018			1 / 1	