

CRIMPFIX R VARIO**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



- For automatic stripping and crimping
- Time-saving and efficient processing
- Easily adjustable to the respective cross-section range
- Stripping and crimping in one work step
- The processing of sleeves or contacts from other manufacturers can cause machine failures and defects!

General ordering data

Type	CRIMPFIX R VARIO
Order No.	258000000
Version	Automatic machines, Automatic stripper and crimper
GTIN (EAN)	4050118605846
Qty.	1 pc(s).

CRIMPFIX R VARIO

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data

Dimensions and weights

Width	335 mm	Width (inches)	13.189 inch
Height	565 mm	Height (inches)	22.244 inch
Depth	485 mm	Depth (inches)	19.094 inch
Net weight	25,265 g		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Technical data

Electrical connection	100 - 240 V / 50/60 Hz / 16 VA
-----------------------	-----------------------------------

PW65 maintenance - automatic stripping/crimping

Compressed-air connection	5.5 bar	Consumables	Linked wire-end ferrules
Crimping	Trapezoidal	Crimping length	8/10 mm
Drive	Electropneumatic	Electrical connection	100 - 240 V / 50/60 Hz / 16 VA
Insertion length, min.	27 mm	Length of wire-end ferrule	14/16 mm
Pulse time	approx. 2 s	Stripping range	0.5 - 2.5 mm ² (~ AWG 20-14)
Wire end ferrules cross-section, max.	2.5 mm ²	Wire end ferrules cross-section, min.	0.5 mm ²

Classifications

ETIM 6.0	EC002778	ETIM 7.0	EC002778
eClass 9.0	17-13-01-01	eClass 9.1	17-13-01-01
eClass 10.0	17-13-01-01		

Approvals

ROHS	Conform
------	---------

Downloads

User Documentation	Manual
--------------------	------------------------